



AERIAL CABLES SYSTEM

# DYNAMICAM

## DATASHEET

### STABILIZED HEAD THREE AXES

Camera / Lens supported	Blackmagic Micro Studio 4K Olympus M Zuiko Digital ED 7-14 mm f/2.8 [ Camera powered via cable ]
Max working area	80 x 80 x 35 m
Max speed	3 m/s
Movement	Pan continuous 360°
Control unit	Console camera Console pilot
Power supply	Via cable
Data / Video	Optical fiber and 4K signal via winches
Weight	4,7 kg Camera + Lens
Dimension [ HxWxL ]	400 x 400 x 520 mm

## **CONSOLE CAMERA OPERATOR**

Data	Optical fiber
Remote control	Pan, Tilt, Roll, Focus, and zoom Adjustable speed, ramp and direction
Dimension [ HxWxL ]	70 x 420 x 300 mm

## **CONSOLE PILOT + GUI PROGRAMMABLE "GRAPHICAL USER INTERFACE"**

Joystick	2 per Control unit Manuale [ X,Y,Z ]
Movement	Free on 3 axes Multi-Point programmable and repeatable
Control setting	Joystick
Dimension [ HxWxL ]	70 x 420 x 300 mm
Safety system	Emergency Stop Button Safety Key Programmable Flight Area
Dimension [ HxWxL ]	400 x 400 x 520 mm